

ROAD-VAULT® FLAT TOP

SINGLE WALL (290 L TO 830 L)

The redesigned line of Road-Vault® single wall tanks from Westeel sets the bar for portable and convenient fuel storage.

Their robust design has been engineered to provide environmentally safe mobile transportation of flammable or combustible liquids in a Transport Canada approved container. Easy to install, its portable single wall storage system delivers the standard features your mobile refueling application deserves complete with an ownership on safe transport practices. Best of all it is manufactured by Westeel to provide years of worry free service.

IMPORTANT FEATURES

Embossed heads on 290L to 830L models add stiffening properties

- Circular pump mounts eliminate coating issues
- J-bolt tie down allows for ease of installation and removal (Ratchet strap tie down option is available on 285L to 450L)
- Optional lifting lugs can be used to move the tank with fuel inside
- Three standard fittings included with optional extra fittings available (Four standard fittings on 545L, 680L, 830L)
- Low profile design that can sit in the back of a pickup truck without obstructing the view out of the rear window

(285L to 545L models) ▪ Integral baffle system on 450L, 545L, 680L and 830L models increases structural rigidity and decreases fuel sloshing

OPTIONAL EQUIPMENT

- Heavy duty lifting lugs
- Fluid transfer and metering equipment

ACCORDANCE COMPLIANCE

- CAN/CGSB-43.146 (Mobile IBC)

TYPICAL APPLICATIONS

Agricultural, construction, aviation, industrial, oil and gas, forestry, mining, marine, recreational, as well as rental applications



SPECIFICATIONS

MODEL NUMBER	NOMINAL CAPACITY		MAX. FILL CAPACITY*		HEIGHT		WIDTH		LENGTH		APPROX. DRY WEIGHT		APPROX. WET WEIGHT	
	Imp gal	L	Imp gal	L	in	mm	in	mm	in	mm	lb	kg	lb	kg
MEDIUM TANK PROFILE														
RV290	64	290	60	275	20.7	526	29.3	745	30.7	780	140	64	686	311
RV450	99	450	95	435	20.7	526	29.3	745	47.4	1205	220	100	1067	484
RV545	121	545	114	520	20.7	526	29.3	745	58.5	1485	250	113	1286	583
LARGE TANK PROFILE														
RV680	150	680	144	655	30.9	785	29.3	745	47.4	1205	295	134	1576	715
RV830	183	830	172	785	30.9	785	29.3	745	58.5	1485	320	145	1883	854

Wet Weight calculated @ 95% tank capacity & Specific Gravity = 0.9 (Diesel)

* TC Codes limit the maximum fill capacity of a Mobile IBC to be 95% of the tank capacity



STORAGE SYSTEMS FOR THE WORLD'S MOST VALUABLE RESOURCES

800-665-2099 ▪ lcs@westeel.com
westeel.com [@westeel_1905](https://twitter.com/westeel_1905) [f/Westeel1905](https://facebook.com/Westeel1905)

Westeel Head Office Box 792,
 Winnipeg, MB, Canada R3C 2N5 ▪ 204-233-7133



Consistent with Westeel policy of continued research and development of our products, we reserve the right to modify or change information contained in this publication without notice. 1015-100